



	Mini	Avant	Pro
Power (W)	20W	100W	300W
CRI	96	96	96
TLCI	96	96	96
Colour Temp Range	2,700 - 6,500K	2,700 - 6,500K	2,700 - 6,500K
Dimming	0-100%	0-100%	0-100%
App Control	✓ (Built-in)	✓ (Built-in)	✓ (Built-in)
IP Rating	IP20	IP20	✗
Built-in Battery	✓	✗	✗
Battery Options	Battery: 7.4V 3,000mAh, 22Wh / Power via USB-C	Continuous power supply 12-20 V / V-Lock compatible	Continuous power supply 24-48 V / V-Lock Dual charger (with AC / DC version)
Lux	Up to 7,199lux+ at 1 metre in full 15° spot	Up to 7,969lux+ at 1 metre with lens attached	Up to 16,928lux+ at 1 metre with lens attached
Luminous Flux	1,600lm (6500K) 1,200lm (2700K)	8,500lm (6,500K) 6,000lm (2,700K)	30,000lm (6,500K) 24,000lm (2,700K)
Includes Barndoors	✓ When purchased in a kit	✓ When purchased in a kit	✓ When purchased in a kit
Lighting Effects	✓ (Built-in)	✓ (Built-in)	✓ (Built-in)
360 Degree Tilting Yoke	✗	✗	✓
Fan Sound	26db at 1m	26db at 1m	28db / manual fan switch-off for lower power
Chasis Materials	Aircraft-grade aluminium	Aircraft-grade aluminium	Aircraft-grade aluminium
Wireless Operating Range	20m	20m	20m
Screen	LCD	LCD full colour	LCD removable control panel
Weight	0.43kg	1.25kg	3.7kg
Dimensions (without yoke)	10.2 x 8.4 x 6.4cm	11.7 x 11.7 x 8.1cm	17.8 x 16.5 x 31.2cm
Bowens Mount Compatible	✗	✓ With adapter	✓ As standard